



ETLS-40-18V

CLOSED LENGTH	21.50 IN	546.10 MM
EXTENDED LENGTH	42.25 IN	1073.15 MM
HEIGHT	10.75 IN	273.00 MM
WIDTH	8.10 IN	205.70 MM
WEIGHT		
EXCL. BATTERY	38.75 LBS	17.57 KG
INCL. BATTERY	41.10 LBS	18.64 KG
1 ST STAGE STROKE	12.95 IN	329.00 MM
1 ST STAGE MAX. PUSH FORCE	38.067 LBF	169.33 KN
2 ND STAGE STROKE	8.70 IN	221.00 MM
2 ND STAGE MAX. PUSH FORCE	13.088 LBF	58.21 KN
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



ETLS-40-20V

CLOSED LENGTH	21.50 IN	546.10 MM
EXTENDED LENGTH	42.25 IN	1073.15 MM
HEIGHT	10.75 IN	273.00 MM
WIDTH	8.10 IN	205.70 MM
WEIGHT		
EXCL. BATTERY	38.75 LBS	17.57 KG
INCL. BATTERY	41.95 LBS	19.02 KG
1 ST STAGE STROKE	12.95 IN	329.00 MM
1 ST STAGE MAX. PUSH FORCE	38.067 LBF	169.33 KN
2 ND STAGE STROKE	8.70 IN	221.00 MM
2 ND STAGE MAX. PUSH FORCE	13.088 LBF	58.21 KN
POWER SOURCE OPTION	DEWALT 20V	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	

