


SCHNETZ

Leading manufacturer of
electrical & hydraulic products for
fire protection and industrial doors and gates

Product catalogue



Drives



Manual Spring Drives



Motorized Spring Drives



Motorized Drives:

ATS-MOF

MOF-SR

ATS-MOFE

MOFE-SR

ATS door drives: automatic and manual opening aid for fire protection and industrial doors

SCHNETZ Door Operators	PAGE
Specifications	2
Door drive - Categorization	3
ATS Spring Drives	
ATS Standard Spring Drives	
ATS-100	4
ATS-100-F with holding device	4
ATS 200	5
ATS 200- F with holding device	5
ATS motorized spring drives	
ATS 100	
MOF	6
MOF SR	6
MOFE	6
MOFE SR	6
ATS 200	
MOF	6
MOF SR	7
ATS Motorized Drives	
ATS 300	
MOF	8
MOF SR	8-9
MOFE	10
MOFE SR	10
ATS 400	
MOF	10
MOF SR	11
MOFE	12
MOFE SR	12
ATS 600	
MOF	12
MOF SR	12
ATS 900	
MOF	13
MOF SR	13

ATS DOOR OPERATORS: AUTOMATIC AND MANUAL OPENING AID FOR FIRE PROTECTION AND INDUSTRIAL DOORS

Standard products are shown in the catalogue. However, special versions are also possible.










SPECIFICATIONS

General information		Certification
Operating temperature	-15°C-40°C	CE marked
Closing speed	0.08-0.3 m/s	DIBt (VdS monitored)
Direction of rotation	- On ATS100 and ATS200 only rotating in one direction due to the recoil spring - All automatic opening aids (MOF): direction of rotation possible on both sides	- Locking device - Control board for locking device

NOMENCLATURE

ATS - 300	-	MOF	-	SR	-	###	-	RH	-	V2A	-	230V	Values	Description
													-	Standard: 400V power supply
													230V	Option: 230V power supply
													-	Standard: Aluminum fasteners
													V2A	Option: Stainless steel fasteners
													RH	Gate opening direction: right
													LH	Gate opening direction: left
													-	Standard model
													###	Special edition
													-	Connection with external control required
													SR	Dead man's control (on/off switch) Option to connect to external controller Directly connected to the brake
													-	No automatic opening aid
													MOF	Standard board (including brake)
													MOFE	PCB with adjustable opening force (including brake)
													ATS-100	Max. door weight: 1000 kg Max. door width: 3 m Clamping force: 100-170 N Closing speed: 0.08-0.3 m/s For MOF: Opening force: 280-350 N Opening speed: 0.3-0.4 m/s
													ATS-200	Max. door weight: 1000 kg Max. gate width: 8 m Clamping force: 110-210 N Closing speed: 0.08-0.3 m/s For MOF: Opening force: 220-340 N Opening speed: 0.3-0.4 m/s
													ATS-300	Max. door weight: 1000 kg Max. goal width: unlimited Opening force: 40-450 N Opening speed: 0.3-0.4 m/s
													ATS-400	Max. door weight: 1500 kg Max. goal width: unlimited Opening force: 40-650 N Opening speed: 0.3-0.4 m/s
													ATS-600	Max. Door Weight: 2000 kg Max. goal width: unlimited Opening force: 900 N Opening speed: 0.1-0.3 m/s
													ATS-900	Max. door weight: 3000 kg Max. goal width: unlimited Opening force: 100-1200 N Opening speed: 0.1 m/s
													ATS-030	Max. door weight: 600 kg Max. goal width: unlimited Opening force: 280-380 N Opening speed: 0.7-1.0 m/s

DRIVE CATEGORIZATION

		Drive Type	Max. Goal Weight	Max. opening width	Closing mechanism	Closing force	Opening Force	Opening Speed	Side
Manual opening aid		ATS-100	1000 kg	3m	Recoil spring	100 N – 170 N	n/a	manual	4-5
		ATS-200	1000 kg	8m		110 N – 210 N	n/a	manual	5
Motorized opening aid		ATS-100-MOF	1000 kg	unlimited	Recoil spring	100 N – 170 N	280 N – 350 N	0.3 m/s – 0.35 m/s	6
		ATS-200-MOF	1000 kg			110 N – 210 N	220 N – 340 N	0.3 m/s – 0.35 m/s	6-7
		ATS-300-MOF	1000 kg		Counterweight	n/a	40 N – 450 N	0.3 m/s – 0.35 m/s	8-10
		ATS-400-MOF	1500 kg				40 N – 650 N	0.3 m/s – 0.35 m/s	11-12
		ATS-600-MOF	2000 kg				900 N	0.1 m/s – 0.3 m/s	12-13
		ATS-900-MOF	3000 kg				100 N – 1200 N	0.1 m/s	13-14
		ATS-030-MOF	600 kg				280 N – 380 N	0.7 m/s – 1.0 m/s	n.A.

MANUAL SPRING DRIVES: Opening manually, closing with spring


ATS Door
Operators

ATS-100

Illustration	Article	Item No.	Spring clamping force [N]	Max. permissible clamping force [N] on the timing belt	Remarks
ATS-100: Standard Spring Drive					
	ATS-100-RH	40-100-0-118-RH_M0P0	100-180	600	
	ATS-100-RH_613-V1	40-100-0-118-RH_M0P0_613-V1	100-180	600	
	ATS-100-RH_613-V2	40-100-0-118-RH_M0P0_613-V2	100-180	600	
	ATS-100-RH_624	40-100-0-118-RH_M0P0_624	100-180	600	
	ATS-100-RH-V2A	40-100-1-118-RH_M0P0	100-180	600	Stainless steel fasteners
	ATS-100-RH_644	40-100-0-118-RH_M0P0_644	70-130	400	Opening width: up to 4 m
	ATS-100-RH_648 ATS-100-LH_648	40-100-0-253-RH_M0P0_648 40-100-0-253-LH_M0P0_648	70-130	400	Opening width: up to 4 m
	ATS-100-RH_625 ATS-100-LH_625	40-100-0-256-RH_M0P0_625 40-100-0-256-LH_M0P0_625	70-130	400	Opening width: up to 4 m
	ATS-100-RH_639 ATS-100-LH_639	40-100-0-256-RH_M0P0_639 40-100-0-256-LH_M0P0_639	70-130	400	Opening width: up to 4 m
	ATS-100-RH_646 ATS-100-LH_646	40-100-0-291-RH_M0P0_646 40-100-0-291-LH_M0P0_646	70-130	400	Opening width: up to 4 m

ATS-100-F: Standard spring drive with brake

	ATS-100-F-RH	40-100-0-157-RH_M0P0	100-180	600	with brake
	ATS-100-F-RH_606	40-100-0-247-RH_M0P0_606	100-180	600	with brake
	ATS-100-F-RH_609 ATS-100-F-LH_609	40-100-0-247-RH_M0P0_609 40-100-0-251-LH_M0P0_609	100-180	600	with brake
	ATS-100-F-RH_628	40-100-0-247-RH_M0P0_628	100-180	600	with brake
	ATS-100-F-RH_637 ATS-100-F-LH_637	40-100-0-107-RH_M0P0_637 40-100-0-107-LH_M0P0_637	100-180	600	with brake
	ATS-100-F-RH_640	40-100-0-247-RH_M0P0_640	100-180	600	with brake
	ATS-100-F-RH_647 ATS-100-F-LH_647	40-100-0-296-RH_M0P0_647 40-100-0-296-LH_M0P0_647	100-180	600	with brake
	ATS-100-F-RH_653	40-100-0-247-RH_M0P0_653	100-180	600	with brake




ATS-100-F-RH-V2A

40-100-1-157-RH_M0P0

100-180

600

Stainless steel fasteners



ATS-100-F-RH_558-V2A

40-100-1-164-RH-M0P0_558

100-180

600

Stainless steel fasteners


ATS-100-F-RH_561-V2A

40-100-1-164-RH_M0P0_561

100-180

600

Stainless steel fasteners



ATS-100-F-RH_643







40-100-0-157-RH_M0P0_643

70-130

400

Opening width: up to 4 m with brake

ATS-200

Illustration	Article	Item No.	Spring clamping force [N]	Max. permissible clamping force [N] on the timing belt	Remarks
ATS-200: Standard Spring Drive					
	ATS-200-RH	40-200-0-106-RH_M0P0	120-220	400	
	ATS-200-LH	40-200-0-106-LH_M0P0			
	ATS-200-RH_624	40-200-0-106-RH_M0P0_624	120-200	400	
	ATS-200-LH_624	40-200-0-106-LH_M0P0_624			
	ATS-200-RH_659	40-200-0-106-RH_M0P0_659	120-200	400	
	ATS-200-RH_629	40-200-0-256-RH_M0P0_629	120-220	400	
	ATS-200-LH_629	40-200-0-256-LH_M0P0_629			
	ATS-200-RH_655	40-200-0-305-RH_M0P0_655	120-200	400	
	ATS-200-LH_655	40-200-0-305-LH_M0P0_655			
ATS-200-F: Standard spring drive with brake					
	ATS-200-F-RH	40-200-0-107-RH_M0P0	120-220	400	with brake
	ATS-200-F-LH	40-200-0-107-LH_M0P0			
	ATS-200-F-LH_538	40-200-0-107-LH-M0P0_538	120-220	400	with brake


MOF MOTORIZED SPRING DRIVES: Opening automatically, closing with spring

ATS Door
Operators


ATS-100-MOF

Illustration	Article	Item No.	Opening Force Drive [N]	Spring clamping force [N]	Max. permissible clamping force [N] on the timing belt	Remarks
--------------	---------	----------	-------------------------	---------------------------	--	---------


ATS-100-MOF: Standard motorized spring drive




ATS-100-RH-MOF	40-100-0-118-RH_M1P1	280-350	100-170	600	
ATS-100-LH-MOF	40-100-0-118-LH_M1P1				



ATS-100-RH-MOF-230V	40-100-0-118-RH_M3P1	280-350	100-170	600	
---------------------	----------------------	---------	---------	-----	--




ATS-100-RH-MOF_657	40-100-0-000-RH_M9P1_657	0-350	100-170	600	
--------------------	--------------------------	-------	---------	-----	--




ATS-100-RH-MOF-V2A	40-100-1-118-RH_M1P1	280-350	100-170	600	Stainless steel fasteners
--------------------	----------------------	---------	---------	-----	---------------------------

ATS-100-MOF-SR: Standard motorized spring drive with dead man's control




ATS-100-RH-MOF-SR	40-100-0-118-RH_M1P2	350-280	100-170	600	Dead man's control
-------------------	----------------------	---------	---------	-----	--------------------

ATS-100-MOFE: Standard motorized spring drive with adjustable opening force/speed



ATS-100-RH-MOFE	40-100-0-118-RH_M1P3	0-280	100-170	600	- Max. door weight: 50 – 600 kg - Opening force/speed adjustable
-----------------	----------------------	-------	---------	-----	---

ATS-100-MOFE-SR: Standard motorized spring drive with dead man's control & adjustable opening force / speed




ATS-100-RH-MOFE-SR	40-100-0-118-RH_M1P4	0-280	100-170	600	- Max. door weight: 50 – 600 kg - Opening force/speed adjustable - Dead man's control
--------------------	----------------------	-------	---------	-----	---


ATS-200-MOF

Illustration	Article	Item No.	Opening Force Drive [N]	Spring clamping force [N]	Max. permissible clamping force [N] on the timing belt	Remarks
--------------	---------	----------	-------------------------	---------------------------	--	---------


ATS-200-MOF: Standard motorized spring drive




ATS-200-RH-MOF	40-200-0-106-RH_M1P1	220-340	110-210	400	
ATS-200-LH-MOF	40-200-0-106-LH_M1P1				



ATS-200-RH-MOF-230V	40-200-0-106-RH_M3P1	220-340	110-210	400	
---------------------	----------------------	---------	---------	-----	--




ATS-200-RH-MOF_538	40-200-0-106-RH_M1P1_538	220-340	110-210	400	
--------------------	--------------------------	---------	---------	-----	--




ATS-200-RH-MOF_657	40-200-0-106-RH_M9P1_657	0-350	110-210	400
--------------------	--------------------------	-------	---------	-----

Asynchronous motor with pure aluminium rotor
Locking device and thermal contact separated




ATS-200-RH-MOF_630	40-200-0-106-RH_M1P1_630	220-340	110-210	400
ATS-200-LH-MOF_630	40-200-0-106-LH_M1P1_630			

ATS-200-MOF-SR: Standard motorized spring drive with dead man's control



ATS-200-MOF-SR-RH	40-200-0-106-RH_M1P2	220-340	110-210	400	Dead man's control
ATS-200-MOF-SR-LH	40-200-0-106-LH_M1P2				













ATS-200-MOF-SR-230V-RH	40-200-0-106-RH_M3P2	220-340	110-210	400	Dead man's control
ATS-200-MOF-SR-230V-LH	40-200-0-106-LH_M3P2				


MOF MOTORIZED ACTUATORS: Opening & closing¹ automatically

ATS Door Operators

1) Closing in the event of a fire by means of a counterweight

ATS-300-MOF

Illustration	Article	Item No.	Opening force Drive [N]	Drive element	Max. permissible clamping force [N]	Remarks
ATS-300-MOF: Standard Motorized Drive						
	ATS-300-RH-MOF	40-300-0-118- RH_M1P1	450	Timing Belt 8M15	600	
	ATS-300-RH-MOF-230V	40-300-0-118- RH_M3P1	450	Timing Belt 8M15	600	
	ATS-300-RH-MOF_538	40-300-0-118- RH_M1P1_538	450	Timing Belt 8M15	600	
	ATS-300-RH-MOF_565	40-300-0-118- RH_M1P1_565	450	Timing Belt 8M15	600	
	ATS-300-RH-MOF_571	40-300-0-118- RH_M1P1_571	450	Timing Belt 8M15	600	
	ATS-300-RH-MOF_572	40-300-0-118- RH_M1P1_572	450	Timing Belt 8M15	600	
	ATS-300-RH-MOF_605 ATS-300-LH-MOF_605	40-300-0-118- RH_M1P1_605 40-300-0-118- LH_M1P1_605	450	Timing Belt 8M15	600	
	ATS-300-RH-MOF- 230V_638	40-300-0-118- RH_M3P1_638	450	Timing Belt 8M15	600	
	ATS-300-RH-MOF-V2A	40-300-1-118- RH_M1P1	450	Timing Belt 8M15	600	Stainless steel fasteners
	ATS-300-RH-MOF- 230V-V2A	40-300-1-118- RH_M3P1	450	Timing Belt 8M15	600	Stainless steel fasteners
	ATS-300-RH-MOF- 230V_564	40-300-0-118- RH_M3P1_564	330-650	Reel	---	Opening width: 3.5 m
	ATS-300-RH-MOF_566	40-300-0-118- RH_M1P1_566	470	Chain 1/2" x 5/16"	---	
ATS-300-MOF-SR: Standard motorized drive with dead man's control						
	ATS-300-RH-MOF-SR ATS-300-LH-MOF-SR	40-300-0-118- RH_M1P2 40-300-0-118- LH_M1P2	450	Timing Belt 8M15	600	Dead man's control



ATS-300-RH-MOF-SR-230V


40-300-0-118-RH_M3P2

450

Timing Belt 8M15

600

Dead man's control



ATS-300-RH-MOF-SR_538


40-300-0-118-RH_M1P2_538

450

Timing Belt 8M15

600

Dead man's control



ATS-300-RH-MOF-SR_571


40-300-0-118-RH_M1P2_571

450

Timing Belt 8M15

600

Dead man's control



ATS-300-RH-MOF-SR_572
ATS-300-LH-MOF-SR_572


40-300-0-118-RH_M1P2_572
40-300-0-118-LH_M1P2_572

450

Timing Belt 8M15

600

Dead man's control



ATS-300-RH-MOF-SR_591


40-300-0-118-RH_M1P2_591

450

Timing Belt 8M15

600

Dead man's control



ATS-300-RH-MOF-SR_605
ATS-300-LH-MOF-SR_605


40-300-0-118-RH_M1P2_605
40-300-0-118-LH_M1P2_605

450

Timing Belt 8M15

600

Dead man's control



ATS-300-RH-MOF-SR_638


40-300-0-118-RH_M1P2_638

450

Timing Belt 8M15

600

Dead man's control



ATS-300-RH-MOF-SR_652
ATS-300-LH-MOF-SR_652


40-300-0-118-RH_M1P2_652
40-300-0-118-LH_M1P2_652

450

Timing Belt 8M15

600

Dead man's control



ATS-300-RH-MOF-SR_656


40-300-0-118-RH_M1P2_656

450

Timing Belt 8M15

600

Dead man's control



ATS-300-MOF-SR-RH-572-230V


40-300-0-118-RH_M3P2_572

450

Timing Belt 8M15

600

Dead man's control



ATS-300-RH-MOF-SR-230V_605

40-300-0-118-RH_M3P2_605

450

Timing Belt 8M15

600

Dead man's control



ATS-300-RH-MOF-SR_566





40-300-0-118-RH_M1P2_566

470






Chain 1/2" x 5/16"

Dead man's control


ATS-300-MOFE: Standard motorized drive with adjustable opening force / speed


	ATS-300-RH-MOFE	40-300-0-118-RH_M1P3	40-450	Timing Belt 8M15	600	- Door weight: 50-600 kg - Opening force/speed adjustable
	ATS-300-RH-MOFE_605	40-300-0-118-RH_M1P3_605	40-450	Timing Belt 8M15	600	- Door weight: 50-600 kg - Opening force/speed adjustable
	ATS-300-RH-MOFE_638	40-300-0-118-RH_M1P3_638	40-450	Timing Belt 8M15	600	- Door weight: 50-600 kg - Opening force/speed adjustable
	ATS-300-RH-MOFE_652	40-300-0-118-RH_M1P3_652	40-450	Timing Belt 8M15	600	- Door weight: 50-600 kg - Opening force/speed adjustable

ATS-300-MOFE-SR: Standard motorized drive with dead man's control & adjustable opening force / speed

	ATS-300-RH-MOFE-SR	40-300-0-118-RH_M1P4	40-450	Timing Belt 8M15	600	- Door weight: 50-600 kg - Opening force/speed adjustable - Dead man's control
	ATS-300-RH-MOFE-SR_538	40-300-0-118-RH_M1P4_538	40-450	Timing Belt 8M15	600	- Door weight: 50-600 kg - Opening force/speed adjustable - Dead man's control
	ATS-300-RH-MOFE-SR_605	40-300-0-118-RH_M1P4_605	40-450	Timing Belt 8M15	600	- Door weight: 50-600 kg - Opening force/speed adjustable - Dead man's control
	ATS-300-MOFE-SR-RH-638	40-300-0-118-RH_M1P4_638	40-450	Timing Belt 8M15	600	- Door weight: 50-600 kg - Opening force/speed adjustable - Dead man's control
	ATS-300-MOFE-SR-RH-652 ATS-300-MOFE-SR-LH-652	40-300-0-118-RH_M1P4_652 40-300-0-118-LH_M1P4_652	40-450	Timing Belt 8M15	600	- Door weight: 50-600 kg - Opening force/speed adjustable - Dead man's control

ATS-400-MOF

Illustration	Article	Item No.	Opening force Drive [N]	Drive element	Max. permissible clamping force [N]	Remarks
ATS-400-MOF: Standard Motorized Drive						
	ATS-400-RH-MOF	40-400-0-118-RH_M1P1	650	Timing Belt 8M15	600	




ATS-400-RH-MOF_638

40-400-0-118-
RH_M1P1_638

650

Timing Belt 8M15

600




ATS-400-RH-MOF_652

40-400-0-118-
RH_M1P1_652

650

Timing Belt 8M15

600



ATS-400-RH-MOF_657


40-400-0-000-
RH_M9P1_657

0-600

Timing Belt 8M15

600

Frequency converter
required



ATS-400-RH-MOF_649


40-400-0-000-
RH_M9P1_649

0-620

Chain 1/2" x 5/16"

Frequency converter
required

ATS-400-MOF-SR: Standard motorized drive with dead man's control



ATS-400-RH-MOF-SR
ATS-400-LH-MOF-SR


40-400-0-118-
RH_M1P2
40-400-0-118-
LH_M1P2

650

Timing Belt 8M15

600

Dead man's control



ATS-400-RH-MOF-
SR_538


40-400-0-118-
RH_M1P2_538

650

Timing Belt 8M15

600

Dead man's control



ATS-400-RH-MOF-
SR_571


40-400-0-118-
RH_M1P2_571

650

Timing Belt 8M15

600

Dead man's control



ATS-400-RH-MOF-
SR_572


40-400-0-118-
RH_M1P2_572

650

Timing Belt 8M15

600

Dead man's control



ATS-400-RH-MOF-
SR_605


40-400-0-118-
RH_M1P2_605

650

Timing Belt 8M15

600

Dead man's control



ATS-400-RH-MOF-
SR_638


40-400-0-118-
RH_M1P2_638

650

Timing Belt 8M15

600

Dead man's control



ATS-400-RH-MOF-
SR_652
ATS-400-LH-MOF-
SR_652


40-400-0-118-
RH_M1P2_652
40-400-0-118-
LH_M1P2_652

650

Timing Belt 8M15

600

Dead man's control



ATS-400-RH-MOF-
SR_566


40-400-0-118-
RH_M1P2_566

650

Chain 1/2" x 5/16"

600

Dead man's control



ATS-400-RH-MOF-
SR_656

40-400-0-118-
RH_M1P2_656


450

Timing Belt 8M15

600

Dead man's control

ATS-400-MOFE: Standard motorized drive with adjustable opening force/speed



ATS-400-RH-MOFE

40-400-0-118-
RH_M1P3


40-650

Timing Belt 8M15

600

- Door weight: 50-600 kg
- Opening force/speed adjustable

ATS-400-MOFE-SR: Standard motorized drive with dead man's control & adjustable opening force / speed



ATS-400-MOFE-SR-RH

40-400-0-118-
RH_M1P4

40-650

Timing Belt 8M15


600

- Door weight: 50-600 kg
- Opening force/speed adjustable
- Dead man's control

ATS-600-MOF

Illustration	Article	Item No.	Opening force Drive [N]	Drive element	Max. permissible clamping force [N]	Remarks
--------------	---------	----------	----------------------------	---------------	--	---------

ATS-600-MOF: Standard Motorized Drive




ATS-600-RH-MOF

40-600-0-118-
RH_M2P1

900

Timing Belt 8M15

600




ATS-600-RH-MOF_652

40-600-0-118-
RH_M2P1_652

900

Timing Belt 8M15

600



ATS-600-MOF-RH-638


40-600-0-118-
RH_M2P1_638

900

Timing Belt 8M15

600

ATS-600-MOF SR: Standard motorized drive with dead man's control



ATS-600-RH-MOF-SR


40-600-0-118-
RH_M2P2

900

Timing Belt 8M15

600

Dead man's control



ATS-600-RH-MOF-
SR_538


40-600-0-118-
RH_M2P2_538

900

Timing Belt 8M15

600

Dead man's control



ATS-600-RH-MOF-
SR_638


40-600-0-118-
RH_M2P2_638

900

Timing Belt 8M15

600

Dead man's control



ATS-600-RH-MOF-
SR_62
ATS-600-LH-MOF-
SR_652


40-600-0-118-
RH_M2P2_652
40-600-0-118-
LH_M2P2_652

900

Timing Belt 8M15

600

Dead man's control



ATS-600-RH-MOF-
SR_656


40-600-0-118-
RH_M2P2_656

900

Timing Belt 8M15

600

Dead man's control



ATS-600-RH-MOF-SR_605
ATS-600-LH-MOF-SR_605

40-600-0-118-RH_M2P2_605
40-600-0-118-LH_M2P2_605

900

Timing Belt 8M15


600

Dead man's control

ATS-900-MOF

Illustration	Article	Item No.	Opening force Drive [N]	Drive element	Max. permissible clamping force [N]	Remarks
--------------	---------	----------	-------------------------	---------------	-------------------------------------	---------

ATS-900-MOF: Standard Motorized Drive




ATS-900-RH-MOF

40-900-0-118-RH_M1P1

1200

Timing belt 8M22

800




ATS-900-RH-MOF_657

40-900-0-118-RH_M9P1_657

0-1500

Timing belt 8M22

800



ATS-900-RH-MOF_638


40-900-0-118-RH_M1P1_638

1200

Timing belt 8M22

800

ATS-900-MOF SR: Standard motorized drive with dead man's control



ATS-900-MOF-SR-RH
ATS-900-MOF-SR-LH


40-900-0-118-RH_M1P2
40-900-0-118-LH_M1P2

1200

Timing belt 8M22

800

Dead man's control



ATS-900-RH-MOF-SR_538


40-900-0-118-RH_M1P2_538

1200

Timing belt 8M22

800

Dead man's control



ATS-900-RH-MOF-SR_571


40-900-0-118-RH_M1P2_571

1200

Timing belt 8M22

800

Dead man's control



ATS-900-RH-MOF-SR_591


40-900-0-118-RH_M1P2_591

1200

Timing belt 8M22

800

Dead man's control



ATS-900-RH-MOF-SR_605


40-900-0-118-RH_M1P2_605

1200

Timing belt 8M22

800

Dead man's control



ATS-900-RH-MOF-SR_638

40-900-0-118-RH_M1P2_638

1200

Timing belt 8M22

800

Dead man's control