

1.2210 • 115CrV3 • Silberstahl • Silver Steel

+AC+C+SL

geschliffen • Tol. h8 (bei 2,5 Ø - 3,5 Ø nur gezogen) / ground • tol. h8 (2,5 Ø - 3,5 Ø only cold drawn)

Stablänge / bar length: 2 m

 Stabenden **nicht** angefast / bar ends **not** chamfered

Abmessung / Dia.	Bestand / Stock	Abmessung / Dia.	Bestand / Stock	Abmessung / Dia.	Bestand / Stock
2,500 Ø	1.581 kg	10,100 Ø	434 kg	23,000 Ø	472 kg
2,900 Ø	300 kg	10,500 Ø	291 kg	23,500 Ø	485 kg
2,980 Ø	40 kg	11,000 Ø	1.434 kg	24,000 Ø	962 kg
3,000 Ø	1.024 kg	11,112 Ø	1.058 kg	24,900 Ø	199 kg
3,175 Ø	457 kg	11,500 Ø	196 kg	25,000 Ø	233 kg
3,500 Ø	871 kg	12,000 Ø	1.637 kg	25,400 Ø	1.892 kg
4,000 Ø	1.580 kg	12,100 Ø	673 kg	26,000 Ø	796 kg
4,300 Ø	340 kg	13,500 Ø	868 kg	28,000 Ø	698 kg
4,500 Ø	570 kg	14,000 Ø	1.148 kg	30,000 Ø	6.765 kg
4,760 Ø	1.215 kg	14,100 Ø	493 kg	32,000 Ø	3.086 kg
5,000 Ø	2.716 kg	14,290 Ø	1.132 kg	35,000 Ø	3.550 kg
5,500 Ø	1.026 kg	14,500 Ø	1.455 kg	39,000 Ø	775 kg
5,550 Ø	169 kg	14,900 Ø	245 kg	40,000 Ø	3.946 kg
5,560 Ø	1.443 kg	15,000 Ø	3.273 kg		
6,000 Ø	3.873 kg	15,500 Ø	1.416 kg		
6,100 Ø	484 kg	15,875 Ø	860 kg		
6,350 Ø	1.236 kg	16,000 Ø	5.460 kg		
6,500 Ø	911 kg	16,500 Ø	1.329 kg		
7,000 Ø	1.539 kg	17,000 Ø	1.721 kg		
7,500 Ø	502 kg	17,700 Ø	105 kg		
7,940 Ø	824 kg	18,000 Ø	2.454 kg		
8,000 Ø	7.745 kg	19,000 Ø	1.937 kg		
8,100 Ø	1.178 kg	19,050 Ø	826 kg		
8,200 Ø	16 kg	20,000 Ø	5.562 kg		
8,500 Ø	422 kg	20,500 Ø	731 kg		
9,000 Ø	000 kg	21,000 Ø	645 kg		
9,500 Ø	1.424 kg	21,500 Ø	934 kg		
9,525 Ø	559 kg	22,000 Ø	2.105 kg		
10,000 Ø	4.873 kg	22,225 Ø	251 kg		