

1.2210 • 115CrV3 • Silberstahl • Silver Steel

+AC+C+SL

geschliffen • Tol. h8 (bei 2,5 Ø - 3,5 Ø nur gezogen) / ground • tol. h8 (2,5 Ø - 3,5 Ø only cold drawn)

Stablänge / bar length: 2 m

 Stabenden **nicht** angefast / bar ends **not** chamfered

Abmessung / Dia.	Bestand / Stock	Abmessung / Dia.	Bestand / Stock	Abmessung / Dia.	Bestand / Stock
2,500 Ø	1.581 kg	10,500 Ø	191 kg	22,225 Ø	251 kg
2,900 Ø	300 kg	11,000 Ø	2.711 kg	23,000 Ø	372 kg
2,980 Ø	40 kg	11,112 Ø	1.059 kg	23,500 Ø	485 kg
3,000 Ø	824 kg	11,500 Ø	762 kg	24,000 Ø	3.808 kg
3,175 Ø	457 kg	12,000 Ø	3.536 kg	24,900 Ø	200 kg
3,500 Ø	871 kg	12,100 Ø	673 kg	25,000 Ø	1.014 kg
4,000 Ø	388 kg	12,500 Ø	687 kg	25,400 Ø	1.892 kg
4,300 Ø	340 kg	12,700 Ø	1.366 kg	26,000 Ø	713 kg
4,500 Ø	470 kg	13,000 Ø	1.195 kg	28,000 Ø	504 kg
4,760 Ø	1.215 kg	13,500 Ø	868 kg	30,000 Ø	6.420 kg
5,000 Ø	2.740 kg	14,000 Ø	1.234 kg	32,000 Ø	3.086 kg
5,500 Ø	1.026 kg	14,100 Ø	493 kg	35,000 Ø	3.055 kg
5,550 Ø	169 kg	14,290 Ø	1.132 kg	39,000 Ø	775 kg
5,560 Ø	1.443 kg	14,500 Ø	1.455 kg	40,000 Ø	2.266 kg
6,000 Ø	4.348 kg	14,900 Ø	245 kg		
6,100 Ø	484 kg	15,000 Ø	3.572 kg		
6,350 Ø	1.086 kg	15,500 Ø	1.416 kg		
6,500 Ø	911 kg	15,875 Ø	860 kg		
7,000 Ø	000 kg	16,000 Ø	4.013 kg		
7,500 Ø	302 kg	16,500 Ø	1.329 kg		
7,940 Ø	824 kg	17,000 Ø	1.021 kg		
8,000 Ø	5.497 kg	17,700 Ø	105 kg		
8,100 Ø	1.179 kg	18,000 Ø	000 kg		
8,200 Ø	17 kg	19,000 Ø	1.892 kg		
8,500 Ø	422 kg	19,050 Ø	826 kg		
9,000 Ø	1.189 kg	20,000 Ø	9.479 kg		
9,500 Ø	1.324 kg	20,500 Ø	731 kg		
9,525 Ø	559 kg	21,000 Ø	645 kg		
10,000 Ø	5.287 kg	21,500 Ø	934 kg		
10,100 Ø	434 kg	22,000 Ø	1.492 kg		