

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- Trade name: **Bylapox 5 Min EP <A>**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesives
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:** BYLA GmbH, Industriestr. 12, D-65594 Runkel
- **Further information obtainable from:** Abteilung Umweltschutz, eMail: contact@byla.de
- **1.4 Emergency telephone number:** Tel. +49-(0)-6482-91200, contact@byla.de

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms** GHS07, GHS09
- **Signal word** Warning
- **Hazard-determining components of labelling:**
reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)
reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection / face protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: Bylapox 5 Min EP <A>

(Contd. of page 1)

P321 Specific treatment (see on this label).
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P391 Collect spillage.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:**
Adhesive
Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 50%
CAS: 9003-36-5	reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	< 50%

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen chloride (HCl)

(Contd. on page 3)

GB



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 5 Min EP <A>**

(Contd. of page 2)

- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear fully protective suit.
Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special measures required.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see section 7.
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

9003-36-5 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral	DNEL (Consumer)	6.25 mg/kg /d Long-term – systemic effects
Dermal	DNEL (Consumer)	62.5 mg/kg /d Long-term – systemic effects
	DNEL (Place of work)	104.15 mg/kg /d Long-term – systemic effects
Inhalative	DNEL (Consumer)	8.7 mg/m ³ Long-term – systemic effects
	DNEL (Place of work)	29.39 mg/m ³ Long-term – systemic effects

(Contd. on page 4)

GB

Trade name: Bylapox 5 Min EP <A>

(Contd. of page 3)

· **PNECs**

9003-36-5 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

PNEC (Waste water treatment plant)	10,000 µg/l
PNEC (Sediment of fresh water)	0.294 mg/kg /d
PNEC (Sediment of sea water)	0.0294 mg/kg /d
PNEC (Ground)	0.237 mg/kg /d
PNEC (Water, sporadic release)	0.0254 mg/l
PNEC (Fresh water)	3 µg/l
PNEC (Sea water)	0.3 µg/l

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Protection of hands:**



Protective gloves

· **Material of gloves** Nitrile rubber, NBR

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

Nitrile rubber, NBR

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	Light yellow
Odour:	Characteristic

· **Change in condition**

Initial boiling point and boiling range: > 200 °C

· **Flash point:** > 250 °C

· **Auto-ignition temperature:** 460 °C

· **Decomposition temperature:** > 200 °C

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 5 Min EP <A>**

(Contd. of page 4)

· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Vapour pressure at 20 °C:	< 0.1 hPa
· Density at 20 °C:	1.17 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Viscosity: Dynamic at 25 °C:	7000 - 8000 mPas
· Solvent content: Organic solvents:	0.0 %
Solids content:	100.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Danger of polymerisation.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Irritant gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

25068-38-6 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	11,400 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)

9003-36-5 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	>2,000 mg/kg (Rat)
Dermal	LD50	>400 mg/kg (Rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 5 Min EP <A>**

(Contd. of page 5)

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

25068-38-6 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

LC50/EC50/IC50 (Fishes)	1.3 mg/l 96 h
EC 50 (24h)	220 mg/l (Daphnia magna)

9003-36-5 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

LC50/EC50/IC50 (Fishes)	2.54 mg/l 96 h
LC50/EC50/IC50 (Algae)	1.8 mg/l 72 h
LC50/EC50/IC50 (Daphnia Magna)	2.55 mg/l 48 h
LC50/EC50/IC50 (Bacteria)	>100 mg/l 3 h
NOEC (21 d)	0.3 mg/kg (Daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is not easily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

- **ADR, IATA** UN3082
- **IMDG** Void

(Contd. on page 7)

Trade name: **Bylapox 5 Min EP <A>**

(Contd. of page 6)

- **14.2 UN proper shipping name**
- **ADR**

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))

- **IMDG**
- **IATA**

Void
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class**

9 (M6) Miscellaneous dangerous substances and articles.

- **Label**

9

- **IMDG**

- **Class**

Void

- **IATA**



- **Class**

9 Miscellaneous dangerous substances and articles.

- **Label**

9

- **14.4 Packing group**

- **ADR, IATA**

III

- **IMDG**

Void

- **14.5 Environmental hazards:**

- **Marine pollutant:**

No

- **Special marking (ADR):**

Symbol (fish and tree)

- **Special marking (IATA):**

Symbol (fish and tree)

- **14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and articles.

- **Hazard identification number (Kemler code):** 90

- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

- **Transport/Additional information:**

- **ADR**

- **Limited quantities (LQ)**

5L

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 5 Min EP <A>**

(Contd. of page 7)

· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT \leq 700), REACTION PRODUCT: BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT \leq 700)), 9, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** Abteilung Umweltschutz
- **Contact:** Herr Simon
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- *** Data compared to the previous version altered.**