

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- Trade name: **Bylapox 7285 <A>**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesives
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:** BYLA GmbH, Industriestr. 12, D-65594 Runkel
- **Further information obtainable from:** Abteilung Umweltschutz, eMail: contact@byla.de
- **1.4 Emergency telephone number:** Tel. +49-(0)-6482-91200, contact@byla.de

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms** GHS07, GHS09
- **Signal word** Warning
- **Hazard-determining components of labelling:**
 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)
 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)
 oxirane, mono[(C12-14-alkyloxy)methyl] derivs
- **Hazard statements**
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection / face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P321 Specific treatment (see on this label).
 P337+P313 If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 7285 <A>**

(Contd. of page 1)

- P391 Collect spillage.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Adhesive

- **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	60.0%
CAS: 9003-36-5	reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	24.0%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4	oxirane, mono[(C12-14-alkyloxy)methyl] derivs ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	14.0%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**
 Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
 Immediately wash with water and soap and rinse thoroughly.
 Immediately rinse with water.
- **After eye contact:**
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
 No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
 In case of fire, the following can be released:
 Carbon monoxide (CO)
 Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
 Hydrogen chloride (HCl)

(Contd. on page 3)

CB



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 7285 <A>**

(Contd. of page 2)

- **5.3 Advice for firefighters**
- **Protective equipment:** Wear fully protective suit.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see section 7.
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **DNELs**

9003-36-5 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral	DNEL (Consumer)	6.25 mg/kg /d Long-term – systemic effects
Dermal	DNEL (Consumer)	62.5 mg/kg /d Long-term – systemic effects
	DNEL (Place of work)	104.15 mg/kg /d Long-term – systemic effects
Inhalative	DNEL (Consumer)	8.7 mg/m ³ Long-term – systemic effects
	DNEL (Place of work)	29.39 mg/m ³ Long-term – systemic effects

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 7285 <A>**

(Contd. of page 3)

68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Oral	DNEL (Consumer)	0.5 mg/kg /d Long-term – systemic effects
Dermal	DNEL (Consumer)	0.5 mg/kg /d Long-term – systemic effects
	DNEL (Place of work)	1 mg/kg /d Long-term – systemic effects
Inhalative	DNEL (Consumer)	0.87 mg/m ³ Long-term – systemic effects
	DNEL (Place of work)	3.6 mg/m ³ Long-term – systemic effects

· **PNECs****9003-36-5 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)**

PNEC (Waste water treatment plant)	10,000 µg/l
PNEC (Sediment of fresh water)	0.294 mg/kg /d
PNEC (Sediment of sea water)	0.0294 mg/kg /d
PNEC (Ground)	0.237 mg/kg /d
PNEC (Water, sporadic release)	0.0254 mg/l
PNEC (Fresh water)	3 µg/l
PNEC (Sea water)	0.3 µg/l

68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

PNEC (Waste water treatment plant)	10,000 µg/l
PNEC (Sediment of fresh water)	307.16 mg/kg /d
PNEC (Sediment of sea water)	30.72 mg/kg /d
PNEC (Water, sporadic release)	0.072 mg/l
PNEC (Fresh water)	7 µg/l
PNEC (Sea water)	1 µg/l

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

GB

Trade name: Bylapox 7285 <A>

(Contd. of page 4)

· **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Fluid
· Colour:	Colourless
· Odour:	Characteristic

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	> 200 °C

· **Flash point:** > 100 °C

· **Auto-ignition temperature:** > 400 °C

· **Decomposition temperature:** > 200 °C

· **Ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

· **Vapour pressure at 20 °C:** < 2 hPa

· **Density at 20 °C:** 1.14 g/cm³

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Viscosity:**

· **Dynamic at 20 °C:** 1000 mPas

· **Solvent content:**

· Organic solvents:	0.0 %
· Water:	0.0 %

· **Solids content:** 100.0 %

· **9.2 Other information**

No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

(Contd. on page 6)



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 7285 <A>**

(Contd. of page 5)

- **10.3 Possibility of hazardous reactions** Danger of polymerisation.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Irritant gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

25068-38-6 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	11,400 mg/kg (Rat)
------	------	--------------------

Dermal	LD50	>2,000 mg/kg (Rabbit)
--------	------	-----------------------

9003-36-5 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	>2,000 mg/kg (Rat)
------	------	--------------------

Dermal	LD50	>400 mg/kg (Rat)
--------	------	------------------

68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Oral	LD50	17,100 mg/kg (Rat)
------	------	--------------------

Dermal	LD50	>4,000 mg/kg (Rabbit)
--------	------	-----------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

25068-38-6 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

LC50/EC50/IC50 (Fishes)	1.3 mg/l 96 h
-------------------------	------------------

EC 50 (24h)	220 mg/l (Daphnia magna)
-------------	--------------------------

9003-36-5 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

LC50/EC50/IC50 (Fishes)	2.54 mg/l 96 h
-------------------------	-------------------

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 7285 <A>**

(Contd. of page 6)

LC50/EC50/IC50 (Algae)	1.8 mg/l 72 h
LC50/EC50/IC50 (Daphnia Magna)	2.55 mg/l 48 h
LC50/EC50/IC50 (Bacteria)	>100 mg/l 3 h
NOEC (21 d)	0.3 mg/kg (Daphnia magna)
68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs	
LC50/EC50/IC50 (Fishes)	>100 mg/l 96 h
LC50/EC50/IC50 (Algae)	843.75 mg/l 72 h
LC50/EC50/IC50 (Daphnia Magna)	7.2 mg/l 48 h
LC50/EC50/IC50 (Bacteria)	>100 mg/l 3 h

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is not easily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IATA** UN3082
- **IMDG** Void
- **14.2 UN proper shipping name**

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 7285 <A>**

(Contd. of page 7)

<ul style="list-style-type: none"> · ADR · IMDG · IATA 	<p>3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700), 2,3-epoxypropyl o-tolyl ether)</p> <p>Void</p> <p>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700), 2,3-epoxypropyl o-tolyl ether)</p>
--	--

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

9 (M6) Miscellaneous dangerous substances and articles.

· **Label**

9

· **IMDG**

· **Class**

Void

· **IATA**



· **Class**

9 Miscellaneous dangerous substances and articles.

· **Label**

9

· **14.4 Packing group**

· **ADR, IATA**

III

· **IMDG**

Void

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **Special marking (ADR):**

Symbol (fish and tree)

· **Special marking (IATA):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and articles.

· **Hazard identification number (Kemler code):** 90

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

· **Transport category**

3

(Contd. on page 9)



Printing date 07.04.2023

Revision: 07.04.2023

Trade name: **Bylapox 7285 <A>**

(Contd. of page 8)

· Tunnel restriction code	E
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700), 2,3-EPOXYPROPYL O-TOLYL ETHER), 9, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** Abteilung Umweltschutz
- **Contact:** Herr Simon
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- *** Data compared to the previous version altered.**