



D'&\$\$\$

2 ; Ug_YhZ'F]b['UbX'Fci bX'DUY'7i Hvf'D'&\$\$\$

HWwb]M' gdYV]ZMhcb

> From single item to medium batch production
Max. depth of cut 40mm

Circular cuts from « (\$'Vlg'«%\$\$\$a a - glnY' =
Circular cuts from « (\$'Vlg'«%) \$\$\$a a - glnY' =

The machines P 2000 II and P 2000 III are freestanding machines of robust steel structure type. They cut absolutely neatly, dimensionally accurately and with straight edges, all suitable materials such as rubber felt, cardboard, plastics, fibre materials, graphite of bonded or non bonded type, and similar. Stock Knife adjustment is quick and precise, thanks to the calibrating tool supplied. Diameter setting of the knives is effected through a hand-operated spindle drive.

The figures adjusted can be easily read from a large display. Knife downfeed is ensured by a hydraulic pneumatic feed system.

The cutting speed is infinitely variable by a frequency converter to allow optimal adjustment to the material being cut. Material is held in position by a pneumatically operated quick clamping device. The work space is illuminated.

Dimensions and Weights | P2000

Designation	Cutting range in mm	Dimensions in mm L x W x H	Packing dimensions in mm L x W x H	Approx. Weight net - gross
P 2000 II	40 - 1000	1800 x 1350 x 1920	2350 x 1750 x 2100	570 - 640 kg
P 2000 III	40 - 1500	2500 x 1900 x 1960	2450 x 2050 x 1960	705 - 795 kg

Accessories and spare parts



Cutting blade of tool steel (standard knife)

[Ref.-No. 2001]

> for rubber and similar soft materials



Cutting blade of tool steel (standard knife)

[Ref.-No. 2002]

> fe.g. for fibrous materials, graphite bonded with stainless steel, and all materials where long tool life is important



Cutting wheel with holder


[Ref.-No. 2003]



Cutting wheel with needle bearing

[Ref.-No. 2004]

> for all materials for which the rolling of the cutting wheel brings advantages, such as f. i. soft rubber types and similar materials, graphite etc. (smallest cutting diameter is limited)



Hard-metal cutting wheel with needle bearing

[Ref. No. 2007]



Hold-down disks

> Hold-down disks, for holding down the material to be cut. The softer and thinner the material, the more accurately the hold-down disk will have to be adapted to the cutting diameter.

[Ref.-No. 200710] from 100 to 550mm Ø

[Ref.-No. 200718] from 100 to 950mm Ø



Rack for 18 hold-down disks

[Ref.-No. 2013]

[Illustrations and dimensions may be subject to changes as result of technical progress.]