abitex srl
via del cristo 84
33044 manzano
ud – italy

t +39 0432 746060
www.abitex.eu
info@abitex.eu

natural roots
fr450 - grand melange
08226

Lohnke
Leder und Textil



IT

codice doganale
54077200.
caratteristiche
100% poliestere, altezza cm ± 140, peso ± 430 gr/m².
tintura
il prodotto é tinta in filo.
lunghezza pezze
circa 35 mtl., disponibile anche al taglio con maggiorazione.
abrasione
> 50.000 cicli, ISO 12947-2.
solidità alla luce
5, ISO 105 B02.
solidità allo sfregamento
secco 4/5, umido 4, ISO 105 X12.
resistenza alla cucitura
ordito 2 mm, trama 3 mm, ISO 13936-2.
pilling
4, ISO 12945-2.
resistenza al fuoco
1IM - UNI 9175; EN 1021 part 1/2;
BS 7176 + A1 medium hazard; BS 5852 crib 5;
NFPA 260 - Class 1; California TB 117-2013;
IMO MED - Ftp 307 part 8.
solo su richiesta
Class 1 - UNI 9177; Class 1 - EN 13773; NF P 92 507 M1;
DIN 4102 B1; ÖNOM B 3825.
attenzione
questi tessuti sono prodotti con un metodo di tintura artigianale che ne conferisce l'aspetto multitono e l'originalità; proprio per questo motivo possono presentarsi differenze di tono ed intensità da partita a partita. fiammature e punti di tonalità differenti sono caratteristiche di questo tipo di lavorazione. consigliamo di verificare le schede tecniche di tutti i prodotti su www.abitex.eu

EN

customs code
54077200.
features
100% polyester, width cm ± 140, weight ± 430 g/m².
dyeing
yarn dyed product.
roll length
approx. 35 lm , can also be cut-to-length at an extra cost.
abrasion resistance
> 50.000 rubs, ISO 12947-2.
colour fastness to light
5, ISO 105 B02.
fastness to rubbing
dry 4/5, wet 4, ISO 105 X12.
seam slippage
warp 2 mm, weft 3 mm, ISO 13936-2.
pilling
4, ISO 12945-2.
fire resistance
1IM - UNI 9175; EN 1021 part 1/2;
BS 7176 + A1 medium hazard; BS 5852 crib 5;
NFPA 260 - Class 1; California TB 117-2013;
IMO MED - Ftp 307 part 8.
only on request
Class 1 - UNI 9177; Class 1 - EN 13773; NF P 92 507 M1;
DIN 4102 B1; ÖNOM B 3825.
attention
these fabrics are produced through an artisan dyeing process that gives them the originality and the multi-tone look. for this reason color shade and intensity may differ from batch to batch. slubs and different color shades are features of this processing technique. please check the technical data sheets of all products on the abitex website www.abitex.eu


fireproof


imo-med



year guarantee

CAMPIONE GRATUITO NON DESTINATO ALLA VENDITA (ART. 2 DPR 26.10.72 N° 633 E SUCCESSIVE INTEGRAZIONI) ESENTE DDT (ART. 4 C 6 DPR 627/78)